Product Data Sheet QuickTask™ Mop

## QuickTask<sup>™</sup> Mop

## Flat mop with microfiber face

The QuickTask™ range consists of a variety of flat mops that can be easily attached to a choice of flat mop frames and handle assemblies.

The split microfiber terry cloth construction of the TASK0300 mop provides exceptional performance in removing soil, residues and other contaminants from nearly any surface, including polymeric flooring. The microfiber loops are very sorbent, and the mop can be used for application of a wide range of solutions and to mop dry already wet surfaces.



Features	Benefits
Cleanroom laundered	100% polyester knit ensures a low level of particulates
Sorbent multilayer knitted surface	<ul><li>Applies solutions evenly</li><li>Suitable for removal of light soils, residues and biofilms</li></ul>
Highly sorbent	<ul> <li>The most sorbent mop cover in the range</li> <li>Exceptional sorbency and mop-to-dry performance on wet surfaces</li> </ul>

PDSM010 | 101725 | ETR3368





Product Data Sheet QuickTask™ Mop

Part No.	Description	Size	Packaging
TASK0300	QuickTask Mop Microfiber	16" x 5" (406 x 130 mm)	10/bag; 4 bags/case
2740	QuickTask Mop Frame Polypropylene	16" x 4.25" (41 x 11 cm)	1/case
2699P	QuickTask Magnetic Mop Frame Polypropylene	15.5" x 3.75" (40 x 10 cm)	1/case
2906	QuickTask Magnetic Mop Frame Stainless steel	15.5" x 3.75" (40 x 10 cm)	1/case
6208	QuickTask Non-magnetic Mop Frame Stainless steel	15.3" x 2.3" (40 x 6 cm)	1/case

Product Information	
Mop material	Polyester split microfiber blue; woven polyester backing; Woven polyester hemmed edge
Mop construction	Multilayer sewn lamination/sealed border
Packaging materials	Outer bags (OB1), low density polyethylene (LDPE) Case (CS), corrugated fiberboard (PAP)
Chemical compatibility	Compatible with a wide range of chemicals and disinfectants (bleach safe)
Environment	ISO 6-8 Grade B/C/D



TASK0300

## Recycle Symbols

PET

HDPE 22,1







PDSM010 | 101725 | ETR3368

Copyright © 2025 Contec, Inc. All rights reserved.



Product Data Sheet QuickTask™ Mop

Technical Data					
Attribute (units)	Typical Value	Test Method			
Mop weight, dry; (g)	84	CTM004-03			
Sorbent capacity; (mL/mop)	254	CTM004-03			
Particles ≥ 0.5μm; (x10 <sup>6</sup> /mop)	48	CTM006-01			
Fibers ≥ 100μm; (x 10³/mop)	3.3	CTM006-01			
Mop coverage; ft <sup>2</sup> (m <sup>2</sup> )		CTM037-01			
S-Curve	246 (23)				
Place and Pull	202 (19)				
Mop frames	2906, 2699P, 2740, 6208				

Packaging	EA/OB1	OB1/OB2	EA/CS
TASK0300	10	4	40

EA = each; OB = outer bag 1; CS = case

## Notes

- a) The data shown are typical values and should not be used as product specifications.
- b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- c) Current and/or comparison data may be available. Please contact a Contec sales representative for details. Test Methods
- 1. CTM = Refers to Contec Test Method.
- 2. Mop coverage data is based on mop head applying solution such that the mopped surface is visibly wetted across the full mop path with no dry streaking observed, under controlled conditions. It is the responsibility of the user to determine appropriate coverage to ensure surfaces are visibly wet for the contact time required for their specific solution.

PDSM010 | 101725 | ETR3368

Copyright © 2025 Contec, Inc. All rights reserved.

