Product Data Sheet QuickTask™ Mop

QuickTask[™] Mop

Flat mop with foam and polyester face

The QuickTask™ range consists of a variety of flat mops that can be easily attached to a choice of flat mop frames and handle assemblies.

QuickTask TASK0600 is a flat, pad-style mop cover designed for outstanding cleaning performance and exceptional durability. The unique microfiber and foam core construction ensures excellent floor contact, sorbency and superior surface cleaning. The ribbed microfiber face fabric is very sorbent, and the mop can be used for application of a wide range of solutions, and to mop dry already wet surfaces.



Features	Benefits
Unique microfiber face and foam core construction	 Ensures excellent surface conformity, sorbency, and superior surface cleaning Compatible with most common solutions, solvents and disinfectants
Ribbed microfiber face	Allows for exceptional cleaning, solution application, and mop to dry performance
Open-ended style back pocket	Open ending pocket allows for liquid to adequately drain to avoid over saturation

Part No.	Description	Size	Packaging
TASK0600	QuickTask Mop Polyester microfiber/foam	16" x 5" (406 x 130 mm)	1/bag; 40 bags/case
2740	QuickTask Mop Frame Polypropylene	16" x 4.25" (41 x 11 cm)	1/case
2699P	QuickTask Magnetic Mop Frame Polypropylene	15.5" x 3.75" (40 x 10 cm)	1/case
2906	QuickTask Magnetic Mop Frame Stainless steel	15.5" x 3.75" (40 x 10 cm)	1/case
6208	QuickTask Non-magnetic Mop Frame Stainless steel	15.3" x 2.3" (40 x 6 cm)	1/case

PDSM013 | 101725 | ETR3367

Copyright © 2025 Contec, Inc. All rights reserved.



Product Data Sheet QuickTask™ Mop

Product Information				
Mop material	Polyester microfiber fully encapsulated foam core, polyester mesh backing, polyester hemmed edge			
Mop construction	Multi-layer sewn lamination/sealed border			
Packaging materials	Outer bags (OB1), low density polyethylene (LDPE) Case (CS), corrugated fiberboard (PAP)			
Environment	ISO 5-8 Grade C/D			



TASK0600

Recycle Symbols











Technical Data					
Attribute (units)	Typical Value	Test Method			
Mop weight, dry; (g)	46	CTM004-03			
Sorbent capacity; (mL/mop)	438	CTM004-03			
Particles ≥ 0.5μm; (x10 ⁶ /mop)	8.5	CTM006-01			
Fibers ≥ 100μm; (x 10³/mop)	0.134	CTM006-01			
Mop coverage; ft ² (m ²)		CTM037-01			
S-Curve	336 (31)				
Place and Pull	161 (15)				
Mop frames	2906, 2699P, 2740, 6208				

Packaging	EA/OB1	OB1/OB2	EA/CS
TASK0600	40	1	40

EA = each; OB = outer bag 1; CS = case

Notes

- a) The data shown are typical values and should not be used as product specifications.
- b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods

- 1. CTM = Refers to Contec Test Method.
- 2. Mop coverage data is based on mop head applying solution such that the mopped surface is visibly wetted across the full mop path with no dry streaking observed, under controlled conditions. It is the responsibility of the user to determine appropriate coverage to ensure surfaces are visibly wet for the contact time required for their specific solution.

PDSM013 | 101725 | ETR3367

Copyright @ 2025 Contec, Inc. All rights reserved.

